

10' Mod-SM-Long-10 - Specification Sheet

Features

- Dimmable LED task lighting
- Energy efficient LED lighting 5000K
- 6360 Lumens
- CRI 90+
- Integrated Defogger

Construction

- Quality polished edge mirror
- Single phase wire installation, silver backed, copper free
- Construction for surface mounting
- Includes installation hardware



Codes/Standards Applicable

- Conforms to UL Std. 962
- Cert. to CSA Std. C22.2 No.250.0-08
- ETL Intertek 5004931

Electrical System

Mod3636L:

- 120Vac, 60Hz, 55.5W
- Electric Current: 0.46A
- Wattage: 55.5W

Mod4836Center:

- 120Vac, 60Hz, 58W
- Electric Current: 0.48A
- Wattage: 58W

Mod3636R:

- 120Vac, 60Hz, 55.5W
- Electric Current: 0.46A
- Wattage: 55.5W

Model

- 10' Mod-SM-Long-10
- Combo of:
 - MODULAR 3636 Left LED Mirror
 - MODULAR 4836 Center LED Mirror
 - MODULAR 3636 Right LED Mirror

10' Mod-SM-Long-10 - Specification Sheet

Dimensions

Mod3636L:



- Height: 36"
- Width: 36"
- Depth: 1-9/16"

Mod4836Center:

- Height: 36"
- Width: 48"
- Depth: 1-9/16"

Mod3636R:

- Height: 36"
- Width: 36"
- Depth: 1-9/16"



FRONT, BACK & SIDE

MODEL	A	B	C	D	E	F	G
10' Mod-SM-Long-10	120	36	17-7/8	17-7/8	23-7/8	1-3/8	3/16